

SNOOP 3 WALL MOUNT DOWN

WALL MOUNTED LUMINAIRE




- Compatible with MR16, 35 and 50 series LED modules
- Colour temperature options: 2700K, 3000K, 3500K, 4000K, 5000K, tuneWHITE™, WARM DIM, flexiK
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 10°, 15°, 20°, 35°, 60° (depending on LED module)
- Luminous flux: 420lm to 950lm (depending on LED module)
- Supplied with phase/0-10V/DALI dimmable LED driver
- IP66 IK08
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-BEAM, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Optional linear spread lens, colour, light effect filters and honeycomb anti-glare louvre




The information above is at nominal values accuracy of +/- 7%.

FIXTURE COLOUR OPTIONS



REFLECTOR COLOUR OPTIONS



tuneWHITE™ and flexiK are recommended to pair with Soft Lens for better colour mixing effect.

AVAILABLE OPTIONS

LED MODULE




TEMPERATURE



DRIVER




ACCESSORIES




BEAM ANGLE


SINGLE CCT
35 NEST / 50 NEST




WARM DIM
35 NEST / 50 NEST




SINGLE CCT
35 NEST ND+ / 50 NEST ND+



tuneWHITE™ / flexiK
50 NEST



DIMENSIONS (MM)




*Displayed height measurements are for highest point of tilting.

PHOTOMETRICS


SNOOP WALL MOUNT

50 PRO

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	10074	9261	3914	1356
Cone DØ (m)	0.19	0.26	0.6	1.22
E (0°)	2518	2315	979	339
Cone DØ (m)	0.37	0.51	1.19	2.43
E (0°)	1119	1029	435	151
Cone DØ (m)	0.56	0.77	1.79	3.65


Correction Factor : 50C - f = 0.75
50N - f = 0.59
35N - f = 0.47

50 NEST WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	4296	2413	1419	491
Cone DØ (m)	0.19	0.34	0.6	1.22
E (0°)	1074	603	355	123
Cone DØ (m)	0.37	0.68	1.19	2.43
E (0°)	477	268	158	55
Cone DØ (m)	0.56	1.03	1.79	3.65


Correction Factor : 35N - f = 0.74

50 PRO WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER


	Emax (lx)		
	20°	35°	60°
E (0°)	4784	2813	974
Cone DØ (m)	0.34	0.6	1.22
E (0°)	1196	703	244
Cone DØ (m)	0.68	1.20	2.44
E (0°)	532	313	108
Cone DØ (m)	1.02	1.80	3.66

50 PRO tuneWHITE™

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

	Emax (lx)		
	20°	35°	60°
E (0°)	4160	2446	847
Cone DØ (m)	0.34	0.6	1.22
E (0°)	1040	612	212
Cone DØ (m)	0.68	1.19	2.43
E (0°)	462	272	94
Cone DØ (m)	1.03	1.79	3.65

Correction Factor : 50N - f = 0.6

SNOOP 3 WALL MOUNT

ORDERING MATRIX CHART

FITTURE						SINGLE CCT LED MODULE				DRIVER
Type	IP	Shape	Colour	Reflector Color	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
SNOOP-3WM										
	IP IP66	D Down	GR Matt Grey	GR Matt Grey	AGL Anti-Glare Louvre	35N 6W	10 10°	27 2700K	Standard	ND Non-Dim
		UD Up/down	MB Matt Black	MB Matt Black	SL Soft Lens	50N 7.5W	20 20°	30 3000K	PA ProART	PH Phase
					LSL Linear Spread Lens		35 35°	35 3500K		AN 0-10V
							60 60°	40 4000K		DA DALI
								50 5000K		
						35N 5W	15 15°	27 2700K	PA ProART	ND+ PRO Non-Dim
						50N 8.7W	20 20°	30 3000K		
							35 35°	35 3500K		
							60 60°			
						WARM DIM LED MODULE				DRIVER
						35N 6W	10 10°	WD WARM DIM	PA ProART	PH Phase
						50N 7.5W	20 20°			AN 0-10V
							35 35°			DA DALI
							60 60°			
						tuneWHITE™ LED MODULE				DRIVER
						50N 7.5W	20 20°	TW18 tuneWHITE™ 1800K-4000K	PA ProART	DA DALI
							35 35°	TW27 tuneWHITE™ 2700K-6500K		
							60 60°			
						flexiK LED MODULE				DRIVER
						50N 7.5W	20 20°	FK## flexiK	PA ProART	PH Phase
							35 35°			AN 0-10V
							60 60°			DA DALI

Snoop outdoor series will ship at IP66 by default.

example: SNOOP-3WM.IP.D.GR.GR.AGL.50N.35.27.PH
 *Custom RAL colour options available.

denotes the first two digits of preferred CCT ranging from 1800K to 6500K by increment of 100K