


# SNOOP 3 WALL MOUNT UP DOWN


WALL MOUNTED LUMINAIRE



FIXTURE  
COLOUR OPTIONS



REFLECTOR  
COLOUR OPTIONS



*tuneWHITE™ and flexiK are recommended to pair with Soft Lens for better colour mixing effect.*



- Compatible with MR16, 35 and 50 series LED modules
- Colour temperature options: 2700K, 3000K, 3500K, 4000K, 5000K, tuneWHITE™, WARM DIM, flexiK
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 10°, 15°, 20°, 35°, 60° (depending on LED module)
- Luminous flux: 420lm to 950lm (depending on LED module)
- Supplied with phase/0-10V/DALI dimmable LED driver
- IP66 IK08
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-BEAM, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Optional linear spread lens, colour, light effect filters and honeycomb anti-glare louvre
- Flat top to prevent waterlogging



*The information above is at nominal values accuracy of +/-7%.*

## AVAILABLE OPTIONS


### LED MODULE




### TEMPERATURE



### DRIVER




### ACCESSORIES




### BEAM ANGLE


SINGLE CCT  
35 NEST / 50 NEST




WARM DIM  
35 NEST / 50 NEST




SINGLE CCT  
35 NEST ND+ / 50 NEST ND+



tuneWHITE™ / flexiK  
50 NEST



## DIMENSIONS (MM)




*\*Displayed height measurements are for highest point of tilting.*

PHOTOMETRICS


# SNOOP WALL MOUNT

## 50 PRO

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

|             | Emax (lx) |      |      |      |
|-------------|-----------|------|------|------|
|             | 10°       | 20°  | 35°  | 60°  |
| E (0°)      | 10074     | 9261 | 3914 | 1356 |
| Cone DØ (m) | 0.19      | 0.26 | 0.6  | 1.22 |
| E (0°)      | 2518      | 2315 | 979  | 339  |
| Cone DØ (m) | 0.37      | 0.51 | 1.19 | 2.43 |
| E (0°)      | 1119      | 1029 | 435  | 151  |
| Cone DØ (m) | 0.56      | 0.77 | 1.79 | 3.65 |


Correction Factor : 50C - f = 0.75  
50N - f = 0.59  
35N - f = 0.47

## 50 NEST WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

|             | Emax (lx) |      |      |      |
|-------------|-----------|------|------|------|
|             | 10°       | 20°  | 35°  | 60°  |
| E (0°)      | 4296      | 2413 | 1419 | 491  |
| Cone DØ (m) | 0.19      | 0.34 | 0.6  | 1.22 |
| E (0°)      | 1074      | 603  | 355  | 123  |
| Cone DØ (m) | 0.37      | 0.68 | 1.19 | 2.43 |
| E (0°)      | 477       | 268  | 158  | 55   |
| Cone DØ (m) | 0.56      | 1.03 | 1.79 | 3.65 |


Correction Factor : 35N - f = 0.74

## 50 PRO WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER


|             | Emax (lx) |      |      |
|-------------|-----------|------|------|
|             | 20°       | 35°  | 60°  |
| E (0°)      | 4784      | 2813 | 974  |
| Cone DØ (m) | 0.34      | 0.6  | 1.22 |
| E (0°)      | 1196      | 703  | 244  |
| Cone DØ (m) | 0.68      | 1.20 | 2.44 |
| E (0°)      | 532       | 313  | 108  |
| Cone DØ (m) | 1.02      | 1.80 | 3.66 |

## 50 PRO tuneWHITE™

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

|             | Emax (lx) |      |      |
|-------------|-----------|------|------|
|             | 20°       | 35°  | 60°  |
| E (0°)      | 4160      | 2446 | 847  |
| Cone DØ (m) | 0.34      | 0.6  | 1.22 |
| E (0°)      | 1040      | 612  | 212  |
| Cone DØ (m) | 0.68      | 1.19 | 2.43 |
| E (0°)      | 462       | 272  | 94   |
| Cone DØ (m) | 1.03      | 1.79 | 3.65 |

Correction Factor : 50N - f = 0.6

