

# VASARI 6 SQUARE

## WALLWASH

RECESSED SQUARE  
WALLWASH DOWNLIGHT  
LUMINAIRE



FIXTURE  
COLOUR OPTIONS



Matt White



Matt Black

# ELR®

- Compatible with 100, 300 and 500 series LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, tuneWHITE™, WARM DIM
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Luminous flux: 1400lm to 6500lm (depending on LED module)
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- 150mm x 150mm cutout
- Wallwash at 30° with linear spreader lens
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-Beam, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Fitted with IP54 spread lens
- Optional honeycomb anti-glare louvre



The information above is at nominal values accuracy of +/-7%.

### AVAILABLE OPTIONS

#### LED MODULE



100C/P



300P



500P

#### TEMPERATURE



ProART



tuneWHITE™



WARM DIM  
WARM DIM

#### DRIVER



(ND)



(PH)



(AN)



(DA)

#### ACCESSORIES



Honeycomb  
Anti-Glare Louvre

#### BEAM ANGLE

##### WALLWASH




60°


### DIMENSIONS (MM)

\*Displayed height measurements are for highest point of fitting.

100C/P: 173  
300P : 223  
500P : 223



161 x 161




(refer to module driver dimensions)

# VASARI 6 WALLWASH

500 PRO

POLAR DIAGRAM



Meter		Emax (lx)
		60°
1	E (0°)	2199
2	E (0°)	550
3	E (0°)	244

Correction Factor : 300P - f = 0.66

## VASARI 6

### ORDERING MATRIX CHART



FIXTURE					SINGLE CCT LED MODULE				DRIVER
Type	Shape	Angle	Colour	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
<b>VASARI-6</b>	—	—	—	—	—	—	—	—	—
<b>RD</b>	Round	<b>WW</b> WALLWASH	<b>WH</b> Matt White	None	<b>100C</b> 16W	<b>12</b> 12°	<b>27</b> 2700K	Standard	<b>ND</b> Non-Dim
<b>SQ</b>	Square		<b>MB</b> Matt Black	<b>AGL</b> Anti-Glare Louvre	<b>100P</b> 25W	<b>20</b> 20°	<b>30</b> 3000K	<b>PA</b> ProART	<b>PH</b> Phase
						<b>35</b> 35°	<b>40</b> 4000K		<b>AN</b> 0-10V
						<b>60</b> 60°	<b>50</b> 5000K		<b>DA</b> DALI
					<b>300P</b> 37W	<b>15</b> 15°	<b>27</b> 2700K	Standard	<b>ND</b> Non-Dim
					<b>500P</b> 56W	<b>30</b> 30°	<b>30</b> 3000K	<b>PA</b> ProART	<b>PH</b> Phase
						<b>45</b> 45°	<b>40</b> 4000K		<b>AN</b> 0-10V
							<b>50</b> 5000K		<b>DA</b> DALI
							<b>TW</b> tuneWHITE™		
					WARM DIM LED MODULE				DRIVER
					<b>100P</b> 25W	<b>20</b> 20°	<b>WD</b> WARM DIM	<b>PA</b> ProART	<b>PH</b> Phase
						<b>35</b> 35°			<b>AN</b> 0-10V
						<b>60</b> 60°			<b>DA</b> DALI
<i>*10° Beam angle option is only available with 35N and 50N WARM DIM LED Modules.</i>									
					tuneWHITE™ LED MODULE				DRIVER
					<b>100P</b> 25W	<b>20</b> 20°	<b>TW</b> tuneWHITE™	<b>PA</b> ProART	<b>DA</b> DALI
						<b>20</b> 35°			
						<b>60</b> 60°			
					<b>300P</b> 37W	<b>15</b> 15°	<b>TW</b> tuneWHITE™	<b>PA</b> ProART	<b>DA</b> DALI
						<b>30</b> 30°			
						<b>45</b> 45°			

example: VASARI-6.RD.WW.WH.AGL.300P.60.27.DA  
 \*Custom RAL colour options available.