

## ARTIS 3 ROUND TILT

SNOOT MULTI-AXIS TILT  
DOWNLIGHT LUMINAIRE



FIXTURE  
COLOUR OPTIONS



Matt White



Matt Black

- Compatible with 35 and 50 series LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, tuneWHITE™, WARM DIM
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 10°, 15°, 20°, 35°, 60° (depending on LED module)
- Luminous flux: 310lm to 1600lm (depending on LED module)
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- 110mm cutout
- +/-30° multi-axis tilt
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-Beam, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Optional 40° linear lens, colour, light effect filters and honeycomb anti-glare louvre



The information above is at nominal values accuracy of +/-7%.

### AVAILABLE OPTIONS

#### LED MODULE



MR16



35/50N



50C/P

#### TEMPERATURE



ProART



tuneWHITE™



WARM DIM  
WARM DIM

#### DRIVER



(ND)



(PH)



(AN)



(DA)

#### ACCESSORIES



Honeycomb  
Anti-Glare Louvre



Soft Lens




40° Linear  
Lens

#### BEAM ANGLE

##### SINGLE CCT


35 NEST / 50 NEST / 50 CLASSIC / 50 PRO



10° 20° 35° 60°

##### WARM DIM


35 NEST / 50 NEST



10° 20° 35° 60°

##### tuneWHITE™


50 NEST / 50 PRO



20° 35° 60°

##### WARM DIM

50 PRO





20° 35° 60°

### DIMENSIONS (MM)

\*Displayed height measurements are for highest point of tilting.

35N : 70  
50N : 95  
50C/P : 95  
MR16 : 70




(refer to module driver dimensions)

PHOTOMETRICS


# ARTIS 3 ROUND

## 50 PRO

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	9836	9043	3748	1298
Cone DØ (m)	0.19	0.26	0.58	1.09
E (0°)	2459	2260.75	937	324.5
Cone DØ (m)	0.38	0.52	1.16	2.18
E (0°)	1093	1005	416	144
Cone DØ (m)	0.57	0.78	1.74	3.27


Correction Factor : 50C - f = 0.8  
50N - f = 0.63  
35N - f = 0.5

## 50 NEST WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	3178	1785	1050	364
Cone DØ (m)	0.19	0.35	0.58	1.09
E (0°)	794.5	446.25	262.5	91
Cone DØ (m)	0.38	0.70	1.16	2.18
E (0°)	353	198	117	40
Cone DØ (m)	0.57	1.05	1.74	3.27


Correction Factor : 35N - f = 0.74

## 50 PRO WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER


	Emax (lx)		
	20°	35°	60°
E (0°)	4887	2874	995
Cone DØ (m)	0.35	0.58	1.09
E (0°)	1221.75	718.5	248.75
Cone DØ (m)	0.70	1.16	2.18
E (0°)	543	319	111
Cone DØ (m)	1.05	1.74	3.27

## 50 PRO tuneWHITE™

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

	Emax (lx)		
	20°	35°	60°
E (0°)	4249	2499	866
Cone DØ (m)	0.35	0.58	1.09
E (0°)	1062.25	624.75	216.5
Cone DØ (m)	0.70	1.16	2.18
E (0°)	472	278	96
Cone DØ (m)	1.05	1.74	3.27

Correction Factor : 50N - f = 0.6

