


SNOOP 4 SINGLE POINT MOUNT

SINGLE POINT MOUNTED LUMINAIRE



- Compatible with 100CLO, 100CLE and 100PLE series LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, WARM DIM
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 12°, 20°, 35°, 60° (depending on LED module)
- Luminous flux: 1063lm to 3000lm (depending on LED module)
- Supplied with phase, 0-10V, DALI dimmable, with local dimming features
- Full angle adjustable
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- Interchangeable LED module system
- Optional 40° linear lens, soft lens and honeycomb anti-glare louvre



The information above is at nominal values accuracy of +/-7%.

AVAILABLE OPTIONS

LED MODULE



100CLO / 100CLE / 100PLE

TEMPERATURE



DRIVER




ACCESSORIES




BEAM ANGLE

SINGLE CCT
100 CLO / 100 CLE / 100PLE



12° 20° 35° 60°


WARM DIM
100PLE



20° 35° 60°

DIMENSIONS (MM)

*Displayed height measurements are for highest point of tilting.




PHOTOMETRICS


SNOOP SINGLE POINT

50 PRO

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	9629	8852	3669	1271
Cone DØ (m)	0.19	0.26	0.6	1.22
E (0°)	2407	2213	917	318
Cone DØ (m)	0.38	0.52	1.20	2.44
E (0°)	1070	984	408	141
Cone DØ (m)	0.57	0.78	1.80	3.66


Correction Factor : 50C - f = 0.8
50N - f = 0.63
35N - f = 0.5

50 NEST WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	3111	1747	1027	356
Cone DØ (m)	0.19	0.34	0.6	1.22
E (0°)	778	437	257	89
Cone DØ (m)	0.38	0.68	1.20	2.44
E (0°)	346	194	114	40
Cone DØ (m)	0.57	1.02	1.80	3.66


Correction Factor : 35N - f = 0.74

50 PRO tuneWHITE™

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)		
	20°	35°	60°
E (0°)	4160	2446	847
Cone DØ (m)	0.34	0.6	1.22
E (0°)	1040	612	212
Cone DØ (m)	0.68	1.20	2.44
E (0°)	462	272	94
Cone DØ (m)	1.02	1.80	3.66


Correction Factor : 50N - f = 0.6

100 PRO

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

	Emax (lx)			
	12°	20°	35°	60°
E (0°)	27565	10467	5990	1592
Cone DØ (m)	0.22	0.39	0.73	1.67
E (0°)	6891	2617	1498	398
Cone DØ (m)	0.44	0.78	1.46	3.34
E (0°)	3063	1163	666	177
Cone DØ (m)	0.66	1.17	2.19	5.01

Correction Factor : 100C - f = 0.68
100C.LO - f = 0.5

SNOOP SINGLE POINT

ORDERING MATRIX CHART

FIXTURE				SINGLE CCT LED MODULE				DRIVER
Type	Colour	Reflector Color	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
SNOOP-3SPM	---	---	---	---	---	---	---	---
WH	Matt White	WH Matt White	AGL Anti-Glare Louvre	35N 6W	10 10°	27 2700K	Standard	PH Phase
MB	Matt Black	CB Chrome Black	SL Soft Lens	50N 7.5W	20 20°	30 3000K	PA ProART	AN 0-10V
		CG Chrome Gold	LL Linear Lens		35 35°	40 4000K		DA DALI
			LBA Local Brightness Adjuster		60 60°	50 5000K		
				WARM DIM LED MODULE				DRIVER
				35N 6W	10 10°	WD WARM DIM	PA ProART	PH Phase
				50N 7.5W	20 20°			AN 0-10V
					35 35°			DA DALI
					60 60°			
<i>*10° Beam angle option is only available with 35N and 50N WARM DIM LED Modules.</i>								
				tuneWHITE™ LED MODULE				DRIVER
				50N 7.5W	20 20°	TW tuneWHITE™	PA ProART	DA DALI
					35 35°			
					60 60°			

example: SNOOP-3SPM.WH.CG.AGL.50N.38.27.PH

*Custom RAL colour options available.

FIXTURE				SINGLE CCT LED MODULE				DRIVER
Type	Colour	Reflector Color	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
SNOOP-4SPM	---	---	---	---	---	---	---	---
WH	Matt White	MH Matt White	AGL Anti-Glare Louvre	100CLO 13W	12 12°	27 2700K	Standard	ND Non-Dim
MB	Matt Black	CB Chrome Black	SL Soft Lens	100CLE 16W	20 20°	30 3000K	PA ProART	PH Phase
		CG Chrome Gold	LL Linear Lens	100PLE 25W	35 35°	40 4000K		AN 0-10V
			LBA Local Brightness Adjuster		60 60°	50 5000K		DA DALI
				WARM DIM LED MODULE				DRIVER
				100PLE 25W	20 20°	WD WARM DIM	PA ProART	PH Phase
					35 35°			AN 0-10V
					60 60°			DA DALI

example: SNOOP-4SPM.WH.CG.AGL.100PLE.38.27.PH

*Custom RAL colour options available.

*10° Beam angle option is only available with 35N and 50N WARM DIM LED Modules.