

100 PRO tuneWHITE™

25W TUNABLE WHITE
LED MODULE



- Feather weight construction, ~100 grams
- Class 2 LED module with external LED driver
- >80 lm/W module
- Colour rendering index, ProART Ra~95
- 3 steps MacAdam ellipse binning
- ATePS™ smart thermal dimming to protect LED lifetime*
- ComfyEYE aspect provides high quality uniform and comfort light with low stroboscopic optical flicker less than 5%**
- IP40



The information above is at nominal values accuracy of +/-7%.

* ATePS™ Automated Thermal Protection System is the trademark of ELR

** Optical flicker percentage is measured at maximum output. ComfyEYE for NEST is only available with R45 all-in-one LED driver (PH, AN, DA) and 36V COB LED Chipsets

tuneWHITE™ is recommended to pair with Soft Lens for better colour mixing effect.

APPLICATION

- Hotel and galleries
- Offices
- Retail, fashion stores and showroom
- Residential

TECHNOLOGY BENEFITS

- Superior light rendering quality offering balanced white with embedded green and red tone
- Excellent cost savings and quicker ROI
- Quick installation, no costly modification required
- Low maintenance
- Comfort, safety and no glass


AVAILABLE OPTIONS

DRIVER




DALI PART
209

TEMPERATURE




BEAM ANGLE

tuneWHITE™
100 PRO




DIMENSIONS (MM)

*Displayed height measurements are for highest point of fitting.




x : 70
y : 93
c : 78




L171 x W43.5 x H32

100 PRO tuneWHITE™

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

	E _{max} (lx)		
	20°	35°	60°
E (0°)	6977	3993	955
Cone DØ (m)	0.40	0.72	1.73
E (0°)	1744	998	239
Cone DØ (m)	0.80	1.44	3.46
E (0°)	775	444	106
Cone DØ (m)	1.20	2.16	5.19

SYSTEM SPECIFICATIONS

LED Lamp Power	LED System Power	Colour	CCT	Beam Angle	PROART CRI 95		Driver Options
					Intensity (cd)	Luminous Flux	
25W	30W	tuneWHITE™	1800K ~ 4000K	60°	950	1800	DA
			OR	35°	3950	2000	
			2700K ~ 6500K	20°	6950	2000	

the table information is at nominal values accuracy of +/-7%
nominal CRI ~95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	100 PRO tuneWHITE™ Series
Mains voltage	100-240, 50Hz
Colour options	White with gold anodized heatsink
Installation Compatibility	Optional with AR111 mounting brackets
Lifetime	50,000 hours (80% lumen maintenance at Ta = 35°C), B10
Dimming	DALI device type 8
Mains connection	Loop-in-loop-out terminals for convenient connection
Materials	Aluminium, plastic
Fire safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability mark	F
IP code	IP40
Safety class	Class 2
Accessories	AR111
Standards	IEC 62031, IEC 61347-2-13
Regulatory markings	CE, CB, RCM
Weight	100g

LED MODULE				DRIVER	
LED Power	Beam Angle	Colour Temp	CRI	Dimming	
ELR100P 25W	—	—	—	—	
20	20°	TW18 tuneWHITE™ 1800K-4000K	PA ProART	DA DALI	
35	35°	TW27 tuneWHITE™ 2700K-6500K			
60	60°				

example: ELR100P.35.TW27.PA.DA