

VASARI 3 SQUARE TILT TRIMLESS

RECESSED SQUARE TILT
TRIMLESS DOWNLIGHT
LUMINAIRE



- Compatible with MR16, 35 and 50 series LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, tuneWHITE™, WARM DIM
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 10°, 20°, 35°, 60° (depending on LED module)
- Luminous flux: 310lm to 1600lm (depending on LED module)
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- 90mm x 90mm cutout
- +30° tilt
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-Beam, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Optional 40° linear lens, colour, light effect filters and honeycomb anti-glare louvre



The information above is at nominal values accuracy of +/-7%.

FIXTURE COLOUR OPTIONS



REFLECTOR COLOUR OPTIONS



AVAILABLE OPTIONS

LED MODULE




TEMPERATURE



DRIVER




ACCESSORIES




BEAM ANGLE


SINGLE CCT
35 NEST / 50 NEST / 50 CLASSIC / 50 PRO




WARM DIM
35 NEST / 50 NEST



tuneWHITE™
50 NEST / 50 PRO





WARM DIM
50 PRO



DIMENSIONS (MM)

*Displayed height measurements are for highest point of tilting.


35N	: 88
50N	: 113
50C/P	: 113
MR16	: 88




VASARI 3

50 PRO

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	E _{max} (lx)			
	10°	20°	35°	60°
E (0°)	9629	8852	3869	1271
Cone DØ (m)	0.19	0.26	0.6	1.22
E (0°)	2407	2213	917	318
Cone DØ (m)	0.38	0.52	1.20	2.44
E (0°)	1070	984	408	141
Cone DØ (m)	0.57	0.78	1.80	3.66


Correction Factor : 50C - f = 0.8
50N - f = 0.63
35N - f = 0.5

50 NEST WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	E _{max} (lx)			
	10°	20°	35°	60°
E (0°)	3111	1747	1027	356
Cone DØ (m)	0.19	0.34	0.6	1.22
E (0°)	778	437	257	89
Cone DØ (m)	0.38	0.68	1.20	2.44
E (0°)	346	194	114	40
Cone DØ (m)	0.57	1.02	1.80	3.66


Correction Factor : 35N - f = 0.74

50 PRO WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER


	E _{max} (lx)		
	20°	35°	60°
E (0°)	4784	2813	974
Cone DØ (m)	0.34	0.6	1.22
E (0°)	1196	703	244
Cone DØ (m)	0.68	1.20	2.44
E (0°)	532	313	108
Cone DØ (m)	1.02	1.80	3.66

50 PRO tuneWHITE™

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

	E _{max} (lx)		
	20°	35°	60°
E (0°)	4160	2446	847
Cone DØ (m)	0.34	0.6	1.22
E (0°)	1040	612	212
Cone DØ (m)	0.68	1.20	2.44
E (0°)	462	272	94
Cone DØ (m)	1.02	1.80	3.66

Correction Factor : 50N - f = 0.6

VASARI 3

ORDERING MATRIX CHART



FIXTURE							SINGLE CCT LED MODULE				DRIVER	
Type	Trim Options	Shape	Angle	Colour	Reflector Color	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming	
VASARI-3												
	Trim	RD Round	FX Fix	WH Matt White	WH Matt White	None	35N 6W	10 10°	27 2700K	Standard	ND Non-Dim	
X	Trimless	SQ Square	TL Tilt	MB Matt Black	MB Matt Black	AGL Anti-Glare Louvre	50N 7.5W	20 20°	30 3000K	PA ProART	PH Phase	
						SL Soft Lens	50C 10W	35 35°	40 4000K		AN 0-10V	
						LL Linear Lens	50P 13W	60 60°	50 5000K		DA DALI	
						IP IP54						
										WARM DIM LED MODULE		DRIVER
							35N 6W	10 10°	WD WARM DIM	PA ProART	PH Phase	
							50N 7.5W	20 20°			AN 0-10V	
							50P 13W	35 35°			DA DALI	
								60 60°				
*10° Beam angle option is only available with 35N and 50N WARM DIM LED Modules.												
										tuneWHITE™ LED MODULE		DRIVER
							50N 7.5W	20 20°	TW tuneWHITE™	PA ProART	DA DALI	
							50P 13W	35 35°				
								60 60°				

**IP54 seal accessory is only valid for fix angle fixtures only.

example: VASARI-3.X.RD.FX.WH.WH.IP.50P.35.27.DA
 *Custom RAL colour options available.