


VASARI 6 ROUND

WALLWASH

RECESSED ROUND
WALLWASH DOWNLIGHT
LUMINAIRE




- Compatible with 100, 300 and 500 series LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, tuneWHITE™, WARM DIM
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Luminous flux: 1400lm to 6500lm (depending on LED module)
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- 150mm cutout
- Wallwash at 30° with linear spreader lens
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-Beam, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Fitted with IP54 spread lens
- Optional honeycomb anti-glare louvre



The information above is at nominal values accuracy of +/-7%.

AVAILABLE OPTIONS

LED MODULE



100C/P 300P 500P

TEMPERATURE



DRIVER



(ND) (PH) (AN) (DA)

ACCESSORIES



Honeycomb Anti-Glare Louvre

BEAM ANGLE

WALLWASH




60°


DIMENSIONS (MM)

*Displayed height measurements are for highest point of fitting.

100C/P: 173
300P : 223
500P : 223



Cut Ø 150




(refer to module driver dimensions)

VASARI 6 WALLWASH

500 PRO

POLAR DIAGRAM



Meter		Emax (lx)
		60°
1	E (0°)	2199
2	E (0°)	550
3	E (0°)	244

Correction Factor : 300P - f = 0.66

VASARI 6

ORDERING MATRIX CHART



FIXTURE					SINGLE CCT LED MODULE				DRIVER
Type	Shape	Angle	Colour	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
VASARI-6									
RD	Round	WW WALLWASH	WH Matt White	None	100C 16W	12 12°	27 2700K	Standard	ND Non-Dim
SQ	Square		MB Matt Black	AGL Anti-Glare Louvre	100P 25W	20 20°	30 3000K	PA ProART	PH Phase
						35 35°	40 4000K		AN 0-10V
						60 60°	50 5000K		DA DALI
					300P 37W	15 15°	27 2700K	Standard	ND Non-Dim
					500P 56W	30 30°	30 3000K	PA ProART	PH Phase
						45 45°	40 4000K		AN 0-10V
							50 5000K		DA DALI
							TW tuneWHITE™		
WARM DIM LED MODULE									DRIVER
					100P 25W	20 20°	WD WARM DIM	PA ProART	PH Phase
						35 35°			AN 0-10V
						60 60°			DA DALI
<i>*10° Beam angle option is only available with 35N and 50N WARM DIM LED Modules.</i>									
tuneWHITE™ LED MODULE									DRIVER
					100P 25W	20 20°	TW tuneWHITE™	PA ProART	DA DALI
						20 35°			
						60 60°			
					300P 37W	15 15°	TW tuneWHITE™	PA ProART	DA DALI
						30 30°			
						45 45°			

example: VASARI-6.RD.WW.WH.AGL.300P.60.27.DA
 *Custom RAL colour options available.