



FV10E-120 **P65**

SINGLE CCT FLEXIBLE LINEAR LED MODULE



PHOTOMETRICS





CRI	ProART (CRI~95)
SDCM	3 step MacAdam ellipse
Lifetime	Up to 50,000 hours L80 lamp life at Ta = 25°C
Voltage	24V DC
Power Options	19.2W/m
Light Effect	Narrow LED pitch distance for light homogeneity
Luminous Flux	Up to 1932 lm/m
Efficacy	Up to 100.6 lm/W
Operating Temperature	Ta (min) = -20°C, Ta (max) = +50°C
Wire Connection	Supplied with insulated AWG 20 wires at 150mm length
Ingress Protection	IP65
Beam Angle	120°

SPECIFICATIONS

CCT Efficacy (lm/W)	Efficacy	Luminous Flux per meter (lm/m)									
		Default (Max.)	With CVMPS150 Dip Switch Settings *								
	(lm/W)		On "8"	On "7"	On "6"	On "5"	On "4"	On "3"	On "2"	On "1"	
		19.2W/m	17.3W/m	15.4W/m	13.4W/m	11.5W/m	9.6W/m	7.7W/m	5.8W/m	3.8W/m	
2700K	95.8	1840	1656	1325	927	556	278	111	33	7	
3000K	95.8									′	
4000K	100.6	6 1932	1739	1391	974	584	292	117	35	7	
6500K										,	
Correction	Correction Factor 1.00		0.90	0.80	0.70	0.60	0.50	0.40	0.30	0.20	



ORDERING MATRIX

Module		Power	ССТ		Length		Sleeve Option		
FM10E-120	19	19.2W/m	27	2700K	5M	5m Reel*	SS	IP65 Silicon Sleeve	
			30	3000K					
			40	4000K					
			65	6500K					

Example: FM10E-120-19-30-5M-SS

FM10E flexible linear LED strips are supplied with insulated AWG 20 wires at 150mm length on both ends.

*Supplied in standard length of 5m per reel, customised lengths are available upon request and additional charges may apply.

Accessories

Aluminium Tray	Finishing		Length		45° Aluminium Tray		Finishing		Length	
FM10-SS-AT	SL	Silver	1000	1000mm	FM10-SS-AT45		Silver	1000	1000mm	
Example:	FM10-SS-AT-SL-1000 FM10 Silicon Sleeve, Aluminium Tray, Silver, 1000mm				Example:	FM10-SS-AT45-SL-1000 FM10 IP65, 45° Aluminium Tray, Silver, 100				

[⚠] When using CVMPS150 with LED module, the driver / power supply unit capacity must be based on the maximum load of the connected LED module.