



Recessed Round Downlight Luminaire

Modularity and Simplicity



Trim Ø85mm



Narrow Trim Ø80mm



Trimless Ø73mm



AQUILA ALPHA



LED Power 10W / 12W An expansion to the Aquila down light series that is part of the Modular Simplified selection of LED luminaires, adopting ELR's signature Modular Concept design in a simplified manner that incorporates most of ELR's technology and features. Aquila Alpha comes in higher power variations that produce up to 1140lm output in ProART CRI~95. Made to be efficient and durable to suit mass deployment applications with demanding conditions, especially in commercial and hospitality sectors.

Modular Concept Design





Ceiling Safe

A mechanism that allows frontal removal for maintenance without risk of damaging the ceiling.

Heat Management

Efficient passive and natural convection that guarantees the LED lifetime and durability.



Single CCT High colour rendering index



NEW ProART98 Ra~98

nominal CRI ~98, equal to Ra >97~99, R9 > 98

Colour Temperature Options



ProART

ProART Ra~95

nominal CRI ~95, equal to Ra >90~97, R9 > 50

2700K 3000K 3500K 4000K

35° Cut-off angle

Driver Dimming Variation



(ND)

PHASE DIMMABLE (PH)





FIND OUT MORE

This is a Circular Economy Product







Production



and Use



Repair, Renew and Reuse



Promise



FIND OUT MORE